

PTF60

MATERIAL	PTF60 is a virgin PTFE material compounded with glass fibre
DESCRIPTION	It has very low friction but it has good wear-, abrasion resistance. It has very good chemical-, extrusion resistance and compressive strength.
APPLICATION	It's used for many applications in very heavy duty, static or dynamic applications. It can be used in Oil, water and more.
TEMPERATURE	The temperature range is between -200°C and 260°C.

Maximum and minimum working temperature is depending on the specific application criteria

PHYSICAL PROPERTIES	TEST METHOD	UNIT	VALUE
Color			Light blue
Specific gravity	ASTMD792 at 23°C	g/cm ³	2,25
hardness	ASTMD2240 at 23°C	Shore D	60
Tensile strength at break	ASTMD4894 at 23°C	Mpa	19,9
Elongation at break	ASTMD4894 at 23°C	%	292
Service temperature range	/	°C	-200/260

The above values are typical

The information in this datasheet is based on many years of experience in the application of PTF60. However, unknown parameters and conditions may restrict general statements during usage. It is vital that users satisfy themselves as to the suitability of individual products through adequate testing. For this reason and due to the wide range of applications of our products, AST B.V. can accept no liability as to the suitability or correctness of our recommendations in individual cases. The application limits for pressure, temperature and velocity given in this datasheet are maximum values determined in the test laboratory. During practical applications it should be remembered that due to the interaction of the operating parameters, the maximum values must be set correspondingly lower. For exceptional operating conditions, please contact us.